

Milestone Review Flysheet

PDR, CDR, FRR

Institution Name	Massachusetts Institute of Technology
------------------	---------------------------------------

Milestone	CDR
-----------	-----

Vehicle Properties	
Diameter (in)	6.28
Length (in)	124.5
Gross Liftoff Weight (lb)	49.27
Launch Lug/button Size	3/16"
Motor Retention	Stainless Steel Rod

Motor Properties	
Motor Manufacturer	Cesaroni
Motor Designation	L1115
Max/Average Thrust (N/lb)	1713N, 1119N
Total Impulse (N-sec/lb-sec)	5015 Ns
Mass pre/post Burn (lb)	4.4kg, 2.01kg

Stability Analysis	
Center of Pressure (in from nose)	89.95
Center of Gravity (in from nose)	77.09
Static Stability Margin	2.11
Thrust-to-Weight Ratio	8.3
Rail Size (in) / Length (in)	1.5" x 1.5", 8ft

Ascent Analysis	
Rail Exit Velocity (ft/s)	54
Max Velocity (ft/s)	594.6
Max Mach Number	0.53
Max Acceleration (ft/s^2)	503.3
Peak Altitude (ft)	5,015

Recovery System Properties				
Drogue Parachute				
Manufacturer/Model		Surplus Military Pilot		
Size		36"		
Altitude at Deployment (ft)		5,650		
Velocity at Deployment (ft/s)		~20 ft/s depending on wind		
Terminal Velocity (ft/s)		46.35		
Recovery Harness Material		Tubular Nylon		
Harness Size/Thickness (in)		1"		
Recovery Harness Length (ft)		16'		
Harness/Airframe Interfaces		Attached to a 3/8" forged eye bolt in top of payload sabot unit. Eye bolt also attached to webbing that goes to tender descender		
Kinetic Energy During Descent (ft-lb)	Section 1	Section 2	Section 3	Section 4
	1320			

Recovery System Properties				
Main Parachute				
Manufacturer/Model		RocketMan		
Size		8'		
Altitude at Deployment (ft)		500'		
Velocity at Deployment (ft/s)		46.35		
Landing Velocity (ft/s)		13.9		
Recovery Harness Material		Tubular Nylon		
Harness Size/Thickness (in)		1"		
Recovery Harness Length (ft)		3.25'		
Harness/Airframe Interfaces		3/8" Forged eye-nut into top of avionics bay, connected to threaded rod into top of motor		
Kinetic Energy Upon Landing (ft-lb)	Section 1	Section 2	Section 3	Section 4
	70.7 (body)	9.8 (Nose/Sabot)	9.7 (Quadrotor)	

Recovery System Properties				
Electronics/Ejection				
Altimeter(s) Make/Model		Featherweight Raven2		
Redundancy Plan		Perfectflite Stratologger, redundant drogue ejection charges. Redundant igniters in Tender Descender on main		
Pad Stay Time (Launch Configuration)		Upwards of 8 hours		

Recovery System Properties		
Electronics/Ejection		
Rocket Locators (Make, Model)	Big Red Bee 70cm Transmitter/2m GPS.	
Transmitting Frequencies	2.4GHz 6 channels 915 Mhz	
Black Power Mass Drogue Parachute (gram)	3.5	
Black Power Mass Main Parachute (gram)	0.2 (Tender Descender release device)	

Milestone Review Flysheet

PDR, CDR, FRR

Institution Name

Massachusetts Institute of Technology

Milestone

CDR

Payload/Science

Succinct Overview of Payload/Science Experiment

A Custom built composite quadrotor carrying a system of payloads to exhibit object tracking and recognition in dynamic environments and to quantitatively measure high-altitude atmospheric lightning events

Identify Major Components

The primary payload of the rocket will be the quadrotor which will be equipped with GPS, radio telecommand devices, an IMU, pressure sensors, an onboard computes, CMOS cameras, IR emitters/detectors, and an autonomous flight stabilizer.

Mass of Payload/Science

The mass of the quadrotor is being estimated to be about 10 pounds.

Test Plan Schedule/Status

Ejection Charge Test(s)

12/14/ 2012 (Successful)

Sub-scale Test Flights

12/15/2012 (Successful)

Full-scale Test Flights

Early February

Additional Comments