Action	Arg's	Description	Example
Move-to	1+	Move message to specified folder. Set message state to *moved*. Optional: specify mailer type.	Move-to inbox Move-to inbox rmail
Copy-to	1+	Copy message to specified folder. Set message state to *copied*. Optional: specify mailer type.	Copy-to inbox Copy-to inbox rmail
Delete	0	Delete message. Set state to *deleted*.	Delete
Remail	1	Forward message to address list.	Remail mackay
Send-me	0	Send message (external server) to me.	Send-me
Runrules	2+	Run specified ruleset on specified folder. Optional: specify mailer type.	Runrules inrules inbox Runrules inrules inbox mh
Stop	0	Stop processing rules in current ruleset.	Stop
Set property	1+	Set user-defined property. Optional: give property a numberical value.	Set important Set important 10
Clear property	1	Clear (remove) specified user property.	Clear important
Add-to	2	Add integer to specified user property.	Add important 3
Subtract-from	2	Subtract integer to specified user property.	Subtract important 3
Permanent	0	Save all user properties on disk.	Permanent
Temporary	0	Delete user properties after running rules.	Temporary
System	1	Execute specified Unix command. Pipe message as standard input.	System zwrite
Systembody	1	Execute specified Unix command. Pipe body of message as standard input.	System lpr
Shell	1	Execute specified shell command. Optional parameters: /n new line /t tab %m message field %u user property %w whole message %b message body %h message header	Shell zwrite "Long Msg: /n %h"