NAME

db_stat – display DB statistics

SYNOPSIS

db_stat [**-lmt**] [**-d file**] [**-h home**]

DESCRIPTION

The *db_stat* utility displays statistics for DB environments.

The options are as follows:

–d Display database statistics for the specified database, as described in *db_open*(3).

–h Specify a home directory for the database.

–l Display log region statistics as described in *db_log*(3).

–m Display shared memory buffer pool statistics as described in *db_mpool*(3).

–t Display transaction region statistics as described in *db_txn*(3).

The *db_stat* utility attaches to DB shared memory regions. In order to avoid region corruption, it should always be given the chance to detach and exit gracefully. To cause *db_stat* to clean up after itself and exit, send it an interrupt signal (SIGINT).

The *db_stat* utility exits 0 on success, and >0 if an error occurs.

ENVIRONMENT VARIABLES

The following environment variables affect the execution of *db_stat*:

DB_HOME

If the **–h** option is not specified and the environment variable *DB_HOME* is set, it is used as the path of the database home, as described in *db_appinit*(3).

SEE ALSO

The DB library is a family of groups of functions that provides a modular programming interface to transactions and record-oriented file access. The library includes support for transactions, locking, logging and file page caching, as well as various indexed access methods. Many of the functional groups (e.g., the file page caching functions) are useful independent of the other DB functions, although some functional groups are explicitly based on other functional groups (e.g., transactions and logging). For a general description of the DB package, see *db_intro*(3).

db_archive(1), *db_checkpoint*(1), *db_deadlock*(1), *db_dump*(1), *db_load*(1), *db_recover*(1), *db_stat*(1), *db_intro*(3), *db_appinit*(3), *db_cursor*(3), *db_dbm*(3), *db_internal*(3), *db_lock*(3), *db_log*(3), *db_mpool*(3), *db_open*(3), *db_thread*(3), *db_txn*(3)