NAME

xwafegopher – a simple x-based gopher client

SYNOPSIS

xwafegopher [**-c** *colormode*] [**-3**] [**-p** *gopher port*] [**-s** *gopher server*]

DESCRIPTION

xwafegopher is a simple x-based gopher client which provides access to the distributed gopher information system by connecting via tcpip to a distant gopher server (default: gopher.micro.umn.edu). xwafegopher is a *wafe* application (see manual page wafeapp) written in Perl.

OPTIONS

In addition to the standard toolkit options such as -display, -name, -geometry, -iconic, -xrm etc. (see manual page X) xwafegopher accepts the following options:

-c *colormode* start xwafegopher using the given color-mode (for details see manual page wafeapp); color modes are for example *mono*, *blueish* or *wheat-ish*.

-3 do not use 3 dimensional widgets. This option depends of the configuration in the system.waferc file (see manual page wafeapp).

-p *gopher port* specify gopher port. The default value is 70.

-s *gopher server* specify name of gopher server. Per default gopher.micro.umn.edu is used.

-h show a short usage message.

LAYOUT and INTERACTION

When xwafegopher is started the user will see an X front end with two main sections: a list of topics and a quit button and an information line. Each item in the list of topics stats with an small symbol to distinguish between text information, directories (lists of subtopics) and telnet based information. The information will be retrieved by clicking with the left mouse button in the line of interest. If an directory was retrieved an additional subwindow pop up, which has the same structure as the top level window. In the current implementation on each level at most one subwindow can be displayed (except for telnet based services). The *Quit* button of the top window terminates the application.

KEY BINDINGS

<Btn1> retrieve information <Btn3> Show source of information

ENVIRONMENT VARIABLES

WAFELIB location of the wafe library (typically /usr/lib/X11/wafe)

PERL VARIABLES

Wafe (Perl-) Variables from $WAFELIB/system.waferc or $HOME/.waferc:

$defaultGopherHost	Name of the default gopher server
$boldFont	typically used for bold labels
$buttonFont	typically used as font for buttons
$buttonAtts	attributes used for buttons
$backGround	back ground color
$roColors	attributes for non emphasized text (typically colors)
$infoColors	attributes of the info line (typically colors)
@textActions	default actions for text widgets

FILES

```
$WAFELIB/system.waferc
$HOME/.waferc
```

SEE ALSO

wafe(n), wafeapp(n), X(1), xwafemail(n), xwafenews(n), xwafeftp(n), xwafeora(n), xwafetel(n), xdirtree(n), xdirtree(n), xprojektor(n), xbm(n), xwafemc(n), xruptimes(n), xnetstats(n), xiostats(n), xvmstats(n), xwafeping(n), xwafecf(n)

COPYRIGHT

Copyright (C) 1992 by Gustaf Neumann, Stefan Nusser


```
Wirtschaftsuniversitaet Wien,
Abteilung fuer Wirtschaftsinformatik
Augasse 2-6,
A-1090 Vienna, Austria
neumann@wu-wien.ac.at, nusser@wu-wien.ac.at
```


Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appears in all copies and that both that copyright notice and this permission notice appear in all supporting documentation. This software is provided "as is" without expressed or implied warranty.

AUTHORS

Gustaf Neumann, Stefan Nusser