NAME

xwafetel – an X-based oracle front–end for a telephone database

SYNOPSIS

xwafetel [**-c** *colormode*] [**-3**] [**-d** *database*] [**-a**] [**-v**]

DESCRIPTION

xwafetel establishes the connection to an Oracle database and allows the user to perform search operations for certain records and displays the found entries.

OPTIONS

In addition to the standard toolkit options such as -display, -name, -geometry, -iconic, -xrm etc. (see manual page X) xwafetel accepts the following options:

-c *colormode*	start xwafetel using the given color-mode (for details see manual page wafeapp); color modes are for example *mono*, *blueish* or *wheat-ish*.
-3	do not use 3 dimensional widgets. This option depends of the configuration in the system.waferc file (see manual page wafeapp).
-d *userid/passwd@T:machine:oracleId*	this option allows the user to specify a different Oracle server and database name to which xwafetel will try to connect.
-a	use the alternative host/database combination from the system.waferc or your local .waferc file.
-v	Print all SQL statements, which are submitted to the oracle server.

LAYOUT and INTERACTION

xwafetel consists of three input fields, one for each corresponding field of the database. The active text widget, which receives all keyboard input, can be recognized by a different background color (if it was not started with -colormode mono) and the insertion caret. The input field can be changed with the <Tab> key. The user can start the searching process by typing the begin of the field and <Return>. For the search only the content of the current active input field is considered. xwafetel will display all entries, which partly or completely match the specified string. If more then one record is found, the user can view the other matches with the keys <arrow up> and <arrow down> or <page up> and <page down>. The application can be terminated using the "quit" button.

KEY BINDINGS

<Key>Up	show previous entry
<Key>Down	show next entry
<Key>Prior	show previous entry
<Key>Next	show next entry
<Key>Return	start a search

ENVIRONMENT VARIABLES

WAFELIB	location of the wafe library (typically /usr/lib/X11/wafe)

PERL VARIABLES

Wafe (Perl-) Variables from $WAFELIB/system.waferc or $HOME/.waferc:

$wafetelDB	specifies the default database
$wafetelDBalt	specifies the alternative default database
$normalFont	used to display the current record
$boldFont	used to display the names of the fields.
$buttonFont	typically used as font for buttons
$buttonAtts	attributes used for buttons
$background	background color
$roColors	attributes for non emphasized text (typically colors)
$highLight	attributes for emphasized text portions (typically colors)
%textResources	default resources for text widgets
@textActions	default actions for text widgets

FILES

```
$WAFELIB/system.waferc
$HOME/.waferc
```

SEE ALSO

wafe(n), wafeapp(n), X(1), xwafemail(n), xwafenews(n), xwafeftp(n), xwafeora(n), xwafetel(n), xdirtree(n), xprojektor(n), xbm(n), xwafemc(n), xruptimes(n), xnetstats(n), xiostats(n), xvmstats(n), xwafeping(n), xwafecf(n)

COPYRIGHT

Wirtschaftsuniversitaet Wien,
Abteilung fuer Wirtschaftsinformatik
Augasse 2-6,
A-1090 Vienna, Austria
neumann@wu-wien.ac.at, nusser@wu-wien.ac.at

AUTHORS

Gustaf Neumann, Stefan Nusser