Kerberos V5 System Administrator's Guide

Release: beta 7
Document Edition: b7-1
Last updated: 10 September 1996

MIT

Copyright © 1990, 1991, 1992, 1993, 1994, 1995, 1996 by the Massachusetts Institute of Technology.

> Export of software employing encryption from the United States of America may require a specific license from the United States Government. It is the responsibility of any person or organization contemplating export to obtain such a license before exporting.

WITHIN THAT CONSTRAINT, permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of M.I.T. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. M.I.T. makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

Kerberos V5 includes documentation and software developed at the University of California at Berkeley, which includes this copyright notice:

Copyright © 1983 Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. All advertising materials mentioning features or use of this software must display the following acknowledgement:

   > This product includes software developed by the University of California, Berkeley and its contributors.

4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notices and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided also that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions.

1 Introduction

1.1 Why Should I use Kerberos?

Since Kerberos negotiates authenticated, and optionally encrypted, communications between two points anywhere on the internet, it provides a layer of security that is not dependent on which side of a firewall either client is on. Since studies have shown that half of the computer security breaches in industry happen from *inside* firewalls, Kerberos V5 from MIT will play a vital role in the security of your network.

1.2 Kerberos V5 Documentation

This document is one piece of the document set for Kerberos V5. The documents, and their intended audiences, are:

This document is one piece of the document set for Kerberos V5. The documents, and their intended audiences, are:

- **Kerberos V5 Installation Guide**: a concise guide for installing Kerberos V5. Kerberos administrators (particularly whoever will be making site-wide decisions about the installation) and the system administrators who will be installing the software should read this guide.
- **Kerberos V5 System Administrator's Guide**: a sysadmin's guide to administering a Kerberos installation. The System Administrator's Guide describes the administration software and suggests policies and procedures for administering a Kerberos installation. Anyone who will have administrative access to your Kerberos database should read this guide.
- **Kerberos V5 UNIX User's Guide**: a guide to using the Kerberos UNIX client programs. All users on UNIX systems should read this guide, particularly the "Tutorial" section.

1.3 Overview of This Guide

The next chapter describes how Kerberos works.

Chapter three describes administration of the principals in the Kerberos database.

Chapter four describes administrative programs for manipulating the Kerberos database as a whole.

Chapter five describes issues to consider when adding an application server to the database.

Chapter six describes our problem reporting system.

The appendices include sample configuration files, the list of Kerberos error messages, and a complete list of the time zones understood by `kadmin`.

2 How Kerberos Works

This section provides a simplified description of a general user's interaction with the Kerberos system. This interaction happens transparently—users don't need to know and probably don't care about what's going on—but Kerberos administrators might find a schematic description of the process useful. This description glosses over a lot of details; for more information, see *Kerberos: An Authentication Service for Open Network Systems*, a paper presented at Winter USENIX 1988, in Dallas, Texas. This paper can be retreived by FTP from `athena-dist.mit.edu`, in the location: `/pub/ATHENA/kerberos/doc/USENIX.ps`.

2.1 Network Services and Their Client Programs

In an environment that provides network services, you use *client* programs to request *services* from *server* programs that are somewhere on the network. Suppose you have logged in to a workstation and you want to '`rlogin`' to a typical UNIX host. You use the local '`rlogin`' client program to contact the remote machine's '`rlogind`' daemon.

2.2 Kerberos Tickets

Under Kerberos, the '`klogind`' daemon allows you to login to a remote machine if you can provide '`klogind`' a Kerberos ticket which proves your identity. In addition to the ticket, you must also have possession of the corresponding ticket session key. The combination of a ticket and the ticket's session key is known as a credential.

Typically, a client program automatically obtains credentials identifying the person using the client program. The credentials are obtained from a Kerberos server that resides somewhere on the network. A Kerberos server maintains a database of user, server, and password information.

2.3 The Kerberos Database

Kerberos will give you credentials only if you have an entry in the Kerberos server's *Kerberos database*. Your database entry includes your Kerberos *principal* (an identifying string, which is often just your username), and your Kerberos password. Every Kerberos user must have an entry in this database.

2.4 Kerberos Realms

Each administrative domain will have its own Kerberos database, which contains information about the users and services for that particular site or administrative domain. This administrative domain is the *Kerberos realm*.

Each Kerberos realm will have at least one Kerberos server, where the master Kerberos database for that site or administrative domain is stored. A Kerberos realm may also have one or more *slave servers*, which have read-only copies of the Kerberos database that are periodically propagated from the master server. For more details on how this is done, see the "Set Up the Slave KDCs for Database Propagation" and "Propagate the Database to Each Slave KDC" sections of the Kerberos V5 Installation Guide.

2.5 The Ticket-Granting Ticket

The '`kinit`' command prompts for your password. If you enter it successfully, you will obtain a *ticket-granting ticket* and a *ticket session key* which gives you the right to use the ticket. This combination of the ticket and its associated key is known as your *credentials*. As illustrated below, client programs use your ticket-granting ticket credentials in order to obtain client-specific credentials as needed.

Your credentials are stored in a *credentials cache*, which is often just a file in `/tmp`. The credentials cache is also called the *ticket file*, especially in Kerberos V4 documentation. Note, however, that a credentials cache does not have to be stored in a file.

2.6 Network Services and the Master Database

The master database also contains entries for all network services that require Kerberos authentication. Suppose that your site has a machine, '`laughter.mit.edu`', that requires Kerberos authentication from anyone who wants to '`rlogin`' to it. The host's Kerberos realm is '`ATHENA.MIT.EDU`'.

This service must be registered in the Kerberos database, using the proper service name, which in this case is the *principal*:

```
host/laughter.mit.edu@ATHENA.MIT.EDU
```

The '`/`' character separates the Kerberos *primary* (in this case, '`host`') from the *instance* (in this case, '`laughter.mit.edu`'); the '`@`' character separates the realm name (in this case, '`ATHENA.MIT.EDU`') from the rest of the principal. The primary, '`host`', denotes the name or type of the service that is being offered: generic host-level access to the machine. The instance, '`laughter.mit.edu`', names the specific machine that is offering this service. There will generally be many different machines, each offering one particular type of service, and the instance serves to give each one of these servers a different Kerberos principal.

2.6.1 The Keytab File

For each service, there must also be a *service key* known only by Kerberos and the service. On the Kerberos server, the service key is stored in the Kerberos database.

On the server host, these service keys are stored in *key tables*, which are files known as *keytabs*.[1] For example, the service keys used by services that run as root are usually stored in the keytab file `/etc/v5srvtab`. **N.B.:** This service key is the equivalent of the service's password, and must be kept secure. Data which is meant to be read only by the service is encrypted using this key.

2.7 The User–Kerberos Interaction

Suppose that you walk up to a host intending to login to it, and then '`rlogin`' to the machine '`laughter`'. Here's what happens:

1. You login to the workstation and use the '`kinit`' command to get a ticket-granting ticket. This command prompts you for your Kerberos password. (On systems running the Kerberos V5 '`login`' program, this may be done as part of the login process, not requiring the user to run a separate program.)
   A. The '`kinit`' command sends your request to the Kerberos master server machine. The server software looks for your principal name's entry in the Kerberos database.
   B. If this entry exists, the Kerberos server creates and returns a ticket-granting ticket and the key which allows you to use it, encrypted by your password. If '`kinit`' can decrypt the Kerberos reply using the password you provide, it stores this ticket in a credentials cache on your local machine for later use. The name of the credentials cache can be specified in the '`KRB5_CCNAME`' environment variable. If this variable is not set, the name of the file will be '`/tmp/krb5cc_<uid>`', where `<uid>` is your UNIX user-id, represented in decimal format.
2. Now you use the '`rlogin`' client to access the machine '`laughter`'.

   `host% rlogin laughter`

   A. The '`rlogin`' client checks your ticket file to see if you have a ticket for the '`host`' service for '`laughter`'. You don't, so '`rlogin`' uses the credential cache's ticket-granting ticket to make a request to the master server's ticket-granting service.
   B. This ticket-granting service receives the request for a ticket for '`host/laughter.mit.edu`', and looks in the master database for an entry for '`host/laughter.mit.edu`'. If the entry exists, the ticket-granting service issues you a ticket for that service. That ticket is also cached in your credentials cache.

[1] Keytabs were called *srvtabs* in Kerberos V4.

C. The '`rlogin`' client now sends that ticket to the '`laughter`' '`klogind`' service program. The service program checks the ticket by using its own service key. If the ticket is valid, it now knows your identity. If you are allowed to login to '`laughter`' (because your username matches one in /etc/passwd, or your Kerberos principal is in the appropriate '`.k5login`' file), `klogind` will let you login.

2.8 Definitions

Following are definitions of some of the Kerberos terminology.

client an entity that can obtain a ticket. This entity is usually either a user or a host.

host a computer that can be accessed over a network.

Kerberos in Greek mythology, the three-headed dog that guards the entrance to the underworld. In the computing world, Kerberos is a network security package that was developed at MIT.

KDC Key Distribution Center. A machine that issues Kerberos tickets.

keytab a **key tab**le file containing one or more keys. A host or service uses a *keytab* file in much the same way as a user uses his/her password.

principal a string that names a specific entity to which a set of credentials may be assigned. It generally has three parts:

- **primary** the first part of a Kerberos *principal*. In the case of a user, it is the username. In the case of a service, it is the name of the service.
- **instance** the second part of a Kerberos *principal*. It gives information that qualifies the primary. The instance may be null. In the case of a user, the instance is often used to describe the intended use of the corresponding credentials. In the case of a host, the instance is the fully qualified hostname.
- **realm** the logical network served by a single Kerberos database and a set of Key Distribution Centers. By convention, realm names are generally all upper-case letters, to differentiate the realm from the internet domain.

The typical format of a typical Kerberos principal is primary/instance@REALM.

service any program or computer you access over a network. Examples of services include "host" (a host, *e.g.*, when you use `telnet` and `rsh`), "ftp" (FTP), "krbtgt" (authentication; cf. *ticket-granting ticket*), and "pop" (email).

ticket a temporary set of electronic credentials that verify the identity of a client for a particular service.

TGT Ticket-Granting Ticket. A special Kerberos ticket that permits the client to obtain additional Kerberos tickets within the same Kerberos realm.

3 Administrating the Kerberos Database

Your Kerberos database contains all of your realm's Kerberos principals, their passwords, and other administrative information about each principal. For the most part, you will use the `kdb5_util` program to manipulate the Kerberos database as a whole, and the `kadmin` program to make changes to the entries in the database. (One notable exception is that users will use the `kpasswd` program to change their own passwords.) The `kadmin` program has its own command-line interface, to which you type the database administrating commands.

`Kdb5_util` provides a means to create, delete, load, or dump a Kerberos database. It also includes a command to stash a copy of the master database key in a file on a KDC, so that the KDC can authenticate itself to the `kadmind` and `krb5kdc` daemons at boot time.

`Kadmin` provides for the maintenance of Kerberos principals, KADM5 policies, and service key tables (keytabs). It exists as both a Kerberos client, `kadmin`, using Kerberos authentication and an RPC, to operate securely from anywhere on the network, and as a local client, `kadmin.local`, intended to run directly on the KDC without Kerberos authentication. Other than the fact that the remote client uses Kerberos to authenticate the person using it, the functionalities of the two versions are identical. The local version is necessary to enable you to set up enough of the database to be able to use the remote version. It replaces the now obsolete `kdb5_edit` (except for database dump and load, which are provided by `kdb5_util`).

The remote version authenticates to the KADM5 server using the service principal `kadmin/admin`. If the credentials cache contains a ticket for the `kadmin/admin` principal, and the '`-c credentials_cache`' option is specified, that ticket is used to authenticate to KADM5. Otherwise, the '`-p`' and '`-k`' options are used to specify the client Kerberos principal name used to authenticate. Once kadmin has determined the principal name, it requests a `kadmin/admin` Kerberos service ticket from the KDC, and uses that service ticket to authenticate to KADM5.

3.1 Kadmin Options

You can invoke `kadmin` with any of the following options:

-r *REALM*
: Use *REALM* as the default Kerberos realm for the database.

-p *principal*
: Use the Kerberos principal *principal* to authenticate to Kerberos. If this option is not given, `kadmin` will append `admin` to either the primary principal name, the environment variable USER, or to the username obtained grom `getpwuid`, in order of preference.

-k *keytab*
: Use the keytab *keytab* to decrypt the KDC response instead of prompting for a password on the TTY. In this case, the principal will be '`host/`*hostname*'.

-c *credentials cache*

Use *credentials_cache* as the credentials cache. The credentials cache should contain a service ticket for the `kadmin/admin` service, which can be acquired with the `kinit` program. If this option is not specified, `kadmin` requests a new service ticket from the KDC, and stores it in its own temporary ccache.

-w *password*

Use *password* as the password instead of prompting for one on the TTY. Note: placing the password for a Kerberos principal with administration access into a shell script can be dangerous if unauthorized users gain read access to the script.

-q *query* Pass *query* directly to `kadmin`. This is useful for writing scripts that pass specific queries to `kadmin`.

3.2 Date Format

Many of the `kadmin` commands take a duration or time as an argument. The date can appear in a wide variety of formats, such as:

```
"15 minutes"
"7 days"
"1 month"
"2 hours"
"400000 seconds"
"next year"
"this Monday"
"next Monday"
yesterday
tomorrow
now
"second Monday"
fortnight
"3/31/92 10:00:07 PST"
"January 23, 1987 10:05pm"
"22:00 GMT"
```

Note that if the date specification contains spaces, you must enclose it in double quotes. Note also that you cannot use a number without a unit. (I.e., ""60 seconds"" is correct, but "60" is incorrect.) All keywords are case-insensitive. The following is a list of all of the allowable keywords.

Months january, jan, february, feb, march, mar, april, apr, may, june, jun, july, jul, august, aug, september, sept, sep, october, oct, november, nov, december, dec

Days sunday, sun, monday, mon, tuesday, tues, tue, wednesday, wednes, wed, thursday, thurs, thur, thu, friday, fri, saturday, sat

Units year, month, fortnight, week, day, hour, minute, min, second, sec

Relative tomorrow, yesterday, today, now, last, this, next, first, third, fourth, fifth, sixth, seventh, eighth, ninth, tenth, eleventh, twelfth, ago

Time Zones
`kadmin` recognizes abbreviations for most of the world's time zones. A complete listing appears in Section A.5 [kadmin Time Zones], page 46.

12-hour Time Delimiters
am, pm

3.3 Principals

Each entry in the Kerberos database contains a Kerberos principal (see Section 2.8 [Definitions], page 6) and the attributes and policies associated with that principal.

3.3.1 Retrieving Information About a Principal

3.3.1.1 Attributes

To retrieve a listing of the attributes and/or policies associated with a principal, use the `kadmin` `get_principal` command, which requires the "inquire" administrative privilege. The syntax is:

get_principal *principal*

The `get_principal` command has the alias `getprinc`.

For example, suppose you wanted to view the attributes of the principals `jennifer/root@ATHENA.MIT.EDU` and `systest@ATHENA.MIT.EDU`. You would type:

```
shell% kadmin
kadmin: getprinc jennifer/root
Principal: jennifer/root@ATHENA.MIT.EDU
Key version: 3
Maximum life: 1 day 00:00:00
Maximum renewable life: 7 days 00:00:00
Master key version: 1
Expires: Mon Jan 18 22:14:07 EDT 2038
Password expires: Mon Sep 19 14:40:00 EDT 1996
Password last changed: Mon Jan 31 02:06:40 EDT 1996
Last modified: by joeadmin/admin@ATHENA.MIT.EDU
on Wed Jul 13 18:27:08 EDT 1996
Attributes: DISALLOW_FORWARDABLE, DISALLOW_PROXIABLE,
REQUIRES_HW_AUTH
Salt type: DEFAULT
kadmin:
```

The `get_principal` command has a `-terse` option, which lists the fields as a quoted, tab-separated string. For example:

```
kadmin: getprinc -terse systest
systest@ATHENA.MIT.EDU 3 86400 604800 1
785926535 753241234 785900000
joeadmin/admin@ATHENA.MIT.EDU 786100034 0
0
kadmin:
```

3.3.1.2 Retrieving a List of Principals

To generate a listing of principals, use the `kadmin list_principals` command, which requires the "list" privilege. The syntax is:

list_principals [*expression*]

where *expression* is a shell-style glob expression that can contain the characters '`*`', '`?`', '`[`', and '`]`'. All policy names matching the expression are displayed. The `list_principals` command has the alias `listprincs`. For example:

```
kadmin: listprincs test*
test3@mit.edu
test2@mit.edu
test1@mit.edu
testuser@mit.edu
kadmin:
```

If no expression is provided, all principals are printed.

3.3.2 Privileges

Administrative privileges for the Kerberos database are stored in the file `kadm5.acl`. Each line of the file contains a principal, the privileges that principal has, and optionally the target to which those permissions apply. The privileges are represented by single letters; UPPER-CASE letters represent negative permissions. The permissions are:

a	allows the addition of principals or policies in the database.
A	disallows the addition of principals or policies in the database.
d	allows the deletion of principals or policies in the database.
D	disallows the deletion of principals or policies in the database.
m	allows the modification of principals or policies in the database.
M	disallows the modification of principals or policies in the database.
c	allows the changing of passwords for principals in the database.
C	disallows the changing of passwords for principals in the database.
i	allows inquiries to the database.

I	disallows inquiries to the database.
l	allows the listing of principals or policies in the database.
L	disallows the listing of principals or policies in the database.
*	All privileges (admcil).
x	All privileges (admcil); identical to "*".

Principals in this file can include the * wildcard. Here is an example of a `kadm5.acl` file. Note that order is important; permissions are determined by the first matching entry.

```
*/admin@ATHENA.MIT.EDU  *
joeadmin/null@ATHENA.MIT.EDU  ADMCIL
joeadmin/*@ATHENA.MIT.EDU  il
jennifer/root@ATHENA.MIT.EDU  cil  */root@ATHENA.MIT.EDU
*/*@ATHENA.MIT.EDU  i
```

In the above file, any principal with an `admin` instance has all administrative privileges. The user `joeadmin` has all permissions with his `admin` instance, `joeadmin/admin@ATHENA.MIT.EDU` (matches the first line). He has no permissions at all with his `null` instance, `joeadmin/null@ATHENA.MIT.EDU` (matches the second line). He has *inquire* and *list* permissions with any other instance (matches the third line). When `jennifer` is using her `root` instance, `jennifer/root@ATHENA.MIT.EDU`, she has *change password*, *inquire*, and *list* privileges for any other principal that has the instance `root`. Finally, any principal in the realm `ATHENA.MIT.EDU` (except for `joeadmin/null@ATHENA.MIT.EDU`, as mentioned above) has *inquire* privileges.

3.3.3 Adding or Modifying Principals

To add a principal to the database, use the kadmin `add_principal` command, which requires the "add" administrative privilege. The syntax is:

kadmin: `add_principal [`*options*`]` *principal*

To modify attributes of a principal, use the kadmin `modify_principal` command, which requires the "modify" administrative privilege. The syntax is:

kadmin: `modify_principal [`*options*`]` *principal*

`add_principal` has the aliases `addprinc` and `ank`[1]. `modify_principal` has the alias `modprinc`.

The `add_principal` and `modify_principal` commands take the following switches:

-salt *salttype*

Uses the specified salt for generating the key. The valid salt types are:

- full_name (aliases "v5_salt" and "normal"; this is the default)
- name_only

[1] `ank` was the short form of the equivalent command using the deprecated `kadmin5` database administrative tool. It has been kept

- realm_only
- no_salt (alias "v4_salt")

-clearpolicy
: removes the current policy from a principal (`modify_principal` only).

-expire *date*
: Sets the expiration date of the principal to *date*.

-pwexpire *date*
: Sets the expiration date of the password to *date*.

-maxlife *maxlife*
: Sets the maximum ticket life of the principal to *maxlife*.

-kvno *number*
: Explicity sets the key version number to *number*. MIT does not recommend doing this unless there is a specific reason.

-policy *policy*
: Sets the policy used by this principal. (See Section 3.4 [Policies], page 16.) If no policy is supplied, the principal will have no policy, and `kadmin` will print a warning message.

{-|+}allow_postdated
: The "-allow_postdated" option prohibits this principal from obtaining postdated tickets. "+allow_postdated" clears this flag. In effect, "-allow_postdated" sets the KRB5_KDB_DISALLOW_POSTDATED flag on the principal in the database.

{-|+}allow_forwardable
: The "-allow_forwardable" option prohibits this principal from obtaining forwardable tickets. "+allow_forwardable" clears this flag. In effect, "-allow_forwardable" sets the KRB5_KDB_DISALLOW_FORWARDABLE flag on the principal in the database.

{-|+}allow_renewable
: The "-allow_renewable" option prohibits this principal from obtaining renewable tickets. "+allow_renewable" clears this flag. In effect, "-allow_renewable" sets the KRB5_KDB_DISALLOW_RENEWABLE flag on the principal in the database.

{-|+}allow_proxiable
: The "-allow_proxiable" option prohibits this principal from obtaining proxiable tickets. "+allow_proxiable" clears this flag. In effect, "-allow_proxiable" sets the KRB5_KDB_DISALLOW_PRC flag. on the principal in the database.

{-|+}allow_dup_skey
: The "-allow_dup_skey" option disables user-to-user authentication for this principal by prohibiting this principal from obtaining a session key for another user. "+allow_dup_skey" clears this flag. In effect, "-allow_dup_skey" sets the KRB5_KDB_DISALLOW_DUP flag on the principal in the database.

{-|+}requires_preauth

The "+requires_preauth" option requires this principal to preauthenticate before being allowed to kinit. -requires_preauth clears this flag. In effect, +requires_preauth sets the KRB5_KDB_REQUIRES_PRE_AUTH flag on the principal in the database.

{-|+}requires_hwauth

The "+requires_hwauth" flag requires the principal to preauthenticate using a hardware device before being allowed to kinit. "-requires_hwauth" clears this flag. In effect, "+requires_hwauth" sets the KRB5_KDB_REQUIRES_HW_AUTH flag on the principal in the database.

{-|+}allow_svr

The "-allow_svr" flag prohibits the issuance of service tickets for this principal. "+allow_svr" clears this flag. In effect, "-allow_svr" sets the KRB5_KDB_DISALLOW_SVR flag on the principal in the database.

{-|+}allow_tgs_req

The "-allow_tgs_req" option specifies that a Ticket-Granting Service (TGS) request for a service ticket for this principal is not permitted. You will probably never need to use this option. "+allow_tgs_req" clears this flag. The default is "+allow_tgs_req". In effect, "-allow_tgs_req" sets the KRB5_KDB_DISALLOW_TGT_BASED flag on the principal in the database.

{-|+}allow_tix

The "-allow_tix" option forbids the issuance of any tickets for this principal. "+allow_tix" clears this flag. The default is "+allow_tix". In effect, "-allow_tix" sets the KRB5_KDB_DISALLOW_AI flag on the principal in the database.

{-|+}needchange

The "+needchange" option sets a flag in attributes field to force a password change; "-needchange" clears it. The default is "-needchange". In effect, "+needchange" sets the KRB5_KDB_REQUIRES_PWCHANGE flag on the principal in the database.

{-|+}password_changing_service

The "+password_changing_service" option sets a flag in the attributes field marking this principal as a password change service. (Again, you will probably never need to use this option.) "-password_changing_service" clears the flag. The default is "-password_changing_service". In effect, the "+password_changing_service" option sets the KRB5_KDB_PWCHANGE_SERVICE flag on the principal in the database.

-clearpolicy *policyname*

Removes the policy *policyname* from the principal (`modify_principal` only).

-randkey Sets the key for the principal to a random value (`add_principal` only). MIT recommends using this option for host keys.

-pw *password*

Sets the key of the principal to the specified string and does not prompt for a password (`add_principal` only). MIT does not recommend using this option.

If you want to just use the default values, all you need to do is:

kadmin: `addprinc jennifer`
WARNING: no policy specified for "jennifer@ATHENA.MIT.EDU";
defaulting to no policy.

Enter password for principal jennifer@ATHENA.MIT.EDU: ⇐ *Type the password.*
Re-enter password for principal jennifer@ATHENA.MIT.EDU: ⇐ *Type it again.*

Principal "jennifer@ATHENA.MIT.EDU" created.
kadmin:

If, on the other hand, you want to set up an account that expires on January 1, 2000, that uses a policy called "stduser", with a temporary password (which you want the user to change immediately), you would type the following. (Note: each line beginning with ⇒ is a continuation of the previous line.)

kadmin: `addprinc david -expire "1/1/2000 12:01am EST" -policy stduser`
⇒ `+needchange`

Enter password for principal david@ATHENA.MIT.EDU: ⇐ *Type the password.*
Re-enter password for principal
david@ATHENA.MIT.EDU: ⇐ *Type it again.*

Principal "david@ATHENA.MIT.EDU" created.
kadmin:

If you will need cross-realm authentication, you need to add principals for the other realm's TGT to each realm. For example, if you need to do cross-realm authentication between the realms ATHENA.MIT.EDU and FUBAR.ORG, you would need to add the principals '`krbtgt/FUBAR.ORG@ATHENA.MIT.ED`' and '`krbtgt/ATHENA.MIT.EDU@FUBAR.ORG`' to both databases. You need to be sure the passwords and the key version numbers (kvno) are the same in both databases. This may require explicitly setting the kvno with the '`-kvno`' option.

3.3.4 Deleting Principals

To delete a principal, use the kadmin `delete_principal` command, which requires the "delete" administrative privilege. The syntax is:

delete_principal `[-force]` *principal*

`delete_principal` has the alias `delprinc`. The `-force` option causes `delete_principal` not to ask if you're sure. For example:

```
kadmin: delprinc jennifer
Are you sure you want to delete the principal
"jennifer@ATHENA.MIT.EDU"? (yes/no): yes
Principal "jennifer@ATHENA.MIT.EDU" deleted.
Make sure that you have removed this principal from
all ACLs before reusing.
kadmin:
```

3.3.5 Changing Passwords

To change a principal's password use the kadmin `change_password` command, which requires the "modify" administrative privilege (unless the principal is changing his/her own password). The syntax is:

change_password [*options*] *principal*

The `change_password` option has the alias `cpw`. `change_password` takes the following options:

-salt *salttype*
: Uses the specified salt for generating the key. Salt types are the same as for the `add_principal` command (see Section 3.3.3 [Adding or Modifying Principals], page 11).

-randkey
: Sets the key of the principal to a random value.

-pw *password*
: Sets the password to the string *password*. MIT does not recommend using this option.

For example:

```
kadmin: cpw david

Enter password for principal david@ATHENA.MIT.EDU:   <= Type the new password.
Re-enter password for principal david@ATHENA.MIT.EDU:   <= Type it again.

Password for david@ATHENA.MIT.EDU changed.
kadmin:
```

Note that `change_password` will not let you change the password to one that is in the principal's password history.

3.3.6 Renaming Principals

To rename a principal, use the kadmin `rename_principal` command, which requires both the "add" and "delete" administrative privileges. The syntax is:

rename_principal [**-force**] *old_principal new_principal*

The `rename_principal` command has the alias `renprinc`.

For example:

kadmin: `renprinc test test0`
Are you sure you want to rename the principal
"test@ATHENA.MIT.EDU" to
"test0@ATHENA.MIT.EDU"? (yes/no): `yes`
Principal "test@ATHENA.MIT.EDU" renamed to
"test0@ATHENA.MIT.EDU".
Make sure that you have removed "test@ATHENA.MIT.EDU" from
all ACLs before reusing.
kadmin:

3.4 Policies

A policy is a set of rules governing passwords. Policies can dictate minimum and maximum password lifetimes, minimum number of characters and character classes a password must contain, and the number of old passwords kept in the database.

3.4.1 Retrieving Policies

To retrieve a policy, use the kadmin `get_policy` command, which requires the "inquire" administrative privilege. The syntax is:

get_policy [**-terse**] *policy*

The `get_policy` command has the alias `getpol`. For example:

kadmin: `get_policy admin`
Policy: admin
Maximum password life: 180 days 00:00:00
Minimum password life: 00:00:00
Minimum password length: 6
Minimum number of password character classes: 2
Number of old keys kept: 5
Reference count: 17
kadmin:

The *reference count* is the number of principals using that policy.

The `get_policy` command has a `-terse` option, which lists each field as a quoted, tab-separated string. For example:

```
kadmin: get_policy -terse admin
admin   15552000      0     6     2     5     17
kadmin:
```

3.4.2 Retrieving the List of Policies

You can retrieve the list of policies with the kadmin `list_policies` command, which requires the "list" privilege. The syntax is:

list_policies [*expression*]

where *expression* is a shell-style glob expression that can contain the characters *, ?, and []. All policy names matching the expression are displayed. The `list_policies` command has the alias `listpols`. For example:

```
kadmin:  listpols
test-pol
dict-only
once-a-min
test-pol-nopw

kadmin:  listpols t*
test-pol
test-pol-nopw
kadmin:
```

3.4.3 Adding or Modifying Policies

To add a new policy, use the kadmin `add_policy` command, which requires the "add" administrative privilege. The syntax is:

add_policy [*options*] *policy_name*

To modify attributes of a principal, use the kadmin `modify_policy` command, which requires the "modify" administrative privilege. The syntax is:

modify_policy [*options*] *policy_name*

`add_policy` has the alias `addpol`. `modify_poilcy` has the alias `modpol`.

The `add_policy` and `modify_policy` commands take the following switches:

-maxlife *time*
: Sets the maximum lifetime of a password to *time*.

-minlife *time*
: Sets the minimum lifetime of a password to *time*.

-minlength *length*
: Sets the minimum length of a password to *length* characters.

-minclasses *number*
: Requires at least *number* of character classes in a password.

-history *number*
: Sets the number of past keys kept for a principal to *number*.

3.4.4 Deleting Policies

To delete a policy, use the `kadmin delete_policy` command, which requires the "delete" administrative privilege. The syntax is:

delete_policy *policy_name*

The `delete_policy` command has the alias `delpol`. It prompts for confirmation before deletion. For example:

```
kadmin: delete_policy guests
Are you sure you want to delete the policy "guests"?
(yes/no): yes
Policy "guests" deleted.
kadmin:
```

Note that you must cancel the policy from all principals before deleting it. The `delete_policy` command will fail if it is in use by any principals.

3.5 Dumping a Kerberos Database to a File

To dump a Kerberos database into a file, use the `kdb5_util dump` command on one of the KDCs. The syntax is:

kdb5_util dump [**-old**] [**-b6**] [**-ov**] [**-verbose**] [*filename* [*principals...*]]

The `kdb5_util dump` command takes the following options:

-old causes the dump to be in the Kerberos 5 Beta 5 and earlier dump format ("kdb5_edit load_dump version 2.0").

-b6 causes the dump to be in the Kerberos 5 Beta 6 format ("kdb5_edit load_dump version 3.0").

-ov causes the dump to be in ovsec_adm_export format.

-verbose causes the name of each principal and policy to be printed as it is dumped.

For example:

```
shell% kdb5_util dump dumpfile
shell%
```

```
shell% kbd5_util dump -verbose dumpfile
kadmin/admin@ATHENA.MIT.EDU
krbtgt/ATHENA.MIT.EDU@ATHENA.MIT.EDU
kadmin/history@ATHENA.MIT.EDU
K/M@ATHENA.MIT.EDU
kadmin/changepw@ATHENA.MIT.EDU
shell%
```

If you specify which principals to dump, you must use the full principal, as in the following example. (The line beginning with ⇒ is a continuation of the previous line.):

```
shell% kdb5_util dump -verbose dumpfile K/M@ATHENA.MIT.EDU
⇒ kadmin/admin@ATHENA.MIT.EDU
kadmin/admin@ATHENA.MIT.EDU
K/M@ATHENA.MIT.EDU
shell%
```

Otherwise, the principals will not match those in the database and will not be dumped:

```
shell% kdb5_util dump -verbose dumpfile K/M kadmin/admin
shell%
```

If you do not specify a dump file, `kdb5_util` will dump the database to the standard output.

3.6 Restoring a Kerberos Database from a Dump File

To restore a Kerberos database dump from a file, use the `kdb5_util load` command on one of the KDCs. The syntax is:

kdb5_util load [-old] [-b6] [-ov] [-verbose] [-update]
dumpfilename dbname [*admin_dbname*]

The `kdb5_util load` command takes the following options:

-old requires the dump to be in the Kerberos 5 Beta 5 and earlier dump format ("kdb5_edit load_dump version 2.0").

-b6 requires the dump to be in the Kerberos 5 Beta 6 format ("kdb5_edit load_dump version 3.0").

-ov requires the dump to be in ovsec_adm_export format.

-verbose causes the name of each principal and policy to be printed as it is dumped.

-update causes records from the dump file to be updated in or added to the existing database.

For example:

```
shell% kdb5_util load dumpfile principal
shell%
```

```
shell% kdb5_util load -update dumpfile principal
shell%
```

If the database file exists, and the **-update** flag was not given, `kdb5_util` will overwrite the existing database.

3.7 Creating a Stash File

A stash file allows a KDC to authenticate itself to the database utilities, such as `kadmin`, `kadmind`, `krb5kdc`, and `kdb5_util`.

To create a stash file, use the `kdb5_util stash` command. The syntax is:

kdb5_util stash [**-f** *keyfile*]

For example:

```
shell% kdb5_util stash
kdb5_util: Cannot find/read stored master key while reading master key
kdb5_util: Warning: proceeding without master key

Enter KDC database master key:    ⇐ Type the KDC database master password.

shell%
```

If you do not specify a stash file, `kdb5_util` will stash the key in the file specified in your `kdc.conf` file.

3.8 Creating and Destroying a Kerberos Database

If you need to create a new Kerberos database, use the `kdb5_util create` command. The syntax is:

kdb5_util create [**-s**]

If you specify the '`-s`' option, `kdb5_util` will stash a copy of the master key in a stash file. (See Section 3.7 [Creating a Stash File], page 20.) For example:

```
shell% /usr/krb5/sbin/kdb5_util -r ATHENA.MIT.EDU create -s
kdb5_util: No such file or directory while setting active database to '/krb5/principal'
Initializing database '/usr/krb5/lib/krb5kdc/principal' for
⇒ realm 'ATHENA.MIT.EDU',
master key name 'K/M@ATHENA.MIT.EDU'
You will be prompted for the database Master Password.
It is important that you NOT FORGET this password.

Enter KDC database master key:    ⇐ Type the master password.
Re-enter KDC database master key to verify:    ⇐ Type it again.

shell%
```

4 Application Servers

If you need to install the Kerberos V5 programs on an application server, please refer to the Kerberos V5 Installation Guide. Once you have installed the software, you need to add that host to the Kerberos database (see Section 3.3.3 [Adding or Modifying Principals], page 11), and generate a *keytab* for that host, that contains the host's key. You also need to make sure the host's clock is within your maximum clock skew of the KDCs.

4.1 Keytabs

A *keytab* is a host's copy of its own keylist, which is analogous to a user's password. An application server that needs to authenticate itself to the KDC has to have a keytab that contains its own principal and key. Just as it is important for users to protect their passwords, it is equally important for hosts to protect their keytabs. You should always store keytab files on local disk, and make them readable only by root, and you should never send a keytab file over a network in the clear. Ideally, you should run the `kadmin` command to extract a keytab on the host on which the keytab is to reside.

4.1.1 Adding Principals to Keytabs

To generate a keytab, or to add a principal to an existing keytab, use the `ktadd` command from `kadmin`, which requires the "inquire" administrative privilege. (If you use the **-glob** *princ_exp* option, it also requires the "list" administrative privilege.) The syntax is:

ktadd [**-k** *keytab*] [**-q**] [*principal* | **-glob** *princ_exp*] [...]

The `ktadd` command takes the following switches:

-k *keytab* use *keytab* as the keytab file. Otherwise, `ktadd` will use the default keytab file (`/etc/v5srvtab`).

-q run in quiet mode. This causes `ktadd` to display less verbose information.

principal | **-glob** *principal expression*
add *principal*, or all principals matching *principal expression* to the keytab. The rules for *principal expression* are the same as for the kadmin `list_principals` (see Section 3.3.1.2 [Retrieving a List of Principals], page 10) command.

For example:

```
kadmin: ktadd host/daffodil.mit.edu@ATHENA.MIT.EDU
kadmin: Entry for principal host/daffodil.mit.edu@ATHENA.MIT.EDU with
    kvno 2, encryption type DES-CBC-CRC added to keytab
    WRFILE:/etc/v5srvtab.
kadmin:
```

kadmin: `ktadd -k /krb5/kadmind.keytab kadmin/admin kadmin/changepw`
kadmin: Entry for principal kadmin/admin@ATHENA.MIT.EDU with kvno 3, encryption type DES-CBC-CRC added to keytab WRFILE:/krb5/kadmind.keytab.
kadmin:

4.1.2 Removing Principals from Keytabs

To remove a principal to an existing keytab, use the kadmin `ktremove` command. The syntax is:

ktremove [**-k** *keytab*] [**-q**] *principal* [*kvno* | **all** | **old**]

The `ktremove` command takes the following switches:

-k *keytab* use *keytab* as the keytab file. Otherwise, `ktremove` will use the default keytab file (`/etc/v5srvtab`).

-q run in quiet mode. This causes `ktremove` to display less verbose information.

principal the principal to remove from the keytab. (Required.)

kvno remove all entries for the specified principal whose Key Version Numbers match *kvno*.

all remove all entries for the specified principal

old remove all entries for the specified principal except those with the highest kvno.

For example:

kadmin: `ktremove -k /krb5/kadmind.keytab kadmin/admin`
kadmin: Entry for principal kadmin/admin with kvno 3 removed from keytab WRFILE:/krb5/kadmind.keytab.
kadmin:

4.2 Clock Skew

In order to prevent intruders from resetting their system clocks in order to continue to use expired tickets, Kerberos V5 is set up to reject ticket requests from any host whose clock is not within the specified maximum clock skew of the KDC (as specified in the `kdc.conf` file). Similarly, hosts are configured to reject responses from any KDC whose clock is not within the specified maximum clock skew of the host (as specified in the `krb5.conf` file). The default value for maximum clock skew is 300 seconds (five minutes).

MIT suggests that you add a line to client machines' `/etc/rc` files to synchronize the machine's clock to your KDC at boot time. On UNIX hosts, assuming you had a kdc called `kerberos` in your realm, this would be:

```
gettime -s kerberos
```

If the host is not likely to be rebooted frequently, you may also want to set up a cron job that adjusts the time on a regular basis.

4.3 Getting DNS Information Correct

Several aspects of Kerberos rely on name service. In order for Kerberos to provide its high level of security, it is less forgiving of name service problems than some other parts of your network. It is important that your Distributed Name Service (DNS) entries and your hosts have the correct information.

Each host's canonical name must be the fully-qualified host name (including the domain), and each host's IP address must reverse-resolve to the canonical name.

Other than the `localhost` entry, make all entries in each machine's `/etc/hosts` file in the following form:

```
IP address      fully-qualified hostname        aliases
```

Here is a sample `/etc/hosts` file:

```
# this is a comment
127.0.0.1       localhost localhost@mit.edu
18.72.0.44       daffodil.mit.edu trillium wake-robin
```

Additionally, on Solaris machines, you need to be sure the "hosts" entry in the file `/etc/nsswitch.conf` includes the source "dns" as well as "file".

Finally, each host's keytab file must include a host/key pair for the host's canonical name. You can list the keys in a keytab file by issuing the command `klist -k`. For example:

```
viola# klist -k
Keytab name: /etc/v5srvtab
KVNO Principal
---- --------------------------------------------------------
   1 host/daffodil.mit.edu@ATHENA.MIT.EDU
```

If you telnet to the host with a fresh credentials cache (ticket file), and then `klist`, the host's service principal should be *host/fully-qualified-hostname@REALM_NAME*.

4.4 Configuring Your Firewall to Work With Kerberos V5

If you need off-site users to be able to get Kerberos tickets in your realm, they must be able to get to your KDC. This requires either that you have a slave KDC outside your firewall, or you configure your firewall to allow UDP requests into to at least one of your KDCs, on whichever port the KDC is running. (The default is port 88; other ports may be specified in the KDC's kdc.conf file.) Similarly, if you need off-site users to be able to change their passwords in your realm, they must be able to get to your Kerberos admin server. The default port for the admin server is 749.

If your on-site users inside your firewall will need to get to KDCs in other realms, you will also need to configure your firewall to allow outgoing TCP and UDP requests to port 88. Additionally, if they will need to get to any Kerberos V4 KDCs, you may also need to allow TCP and UDP requests to port 750. If your on-site users inside your firewall will need to get to Kerberos admin servers in other realms, you will also need to allow outgoing TCP and UDP requests to port 749.

If any of your KDCs is outside your firewall, you will need to allow `kprop` requests to get through to the remote KDC. `Kprop` uses the krb5_prop service on port 754 (tcp).

If you need your off-site users to have access to machines inside your firewall, you need to allow TCP connections from their off-site hosts on the appropriate ports for the programs they will be using. The following lines from `/etc/services` show the default port numbers for the Kerberos V5 programs:

```
ftp             21/tcp                  # Kerberos ftp and telnet use the
telnet          23/tcp                  # default ports
kerberos        88/udp      kdc         # Kerberos V5 KDC
kerberos        88/tcp      kdc         # Kerberos V5 KDC
klogin          543/tcp                 # Kerberos authenticated rlogin
kshell          544/tcp     cmd         # and remote shell
kerberos-adm    749/tcp                 # Kerberos 5 admin/changepw
kerberos-adm    749/udp                 # Kerberos 5 admin/changepw
krb5_prop       754/tcp                 # Kerberos slave propagation
eklogin         2105/tcp                # Kerberos auth. & encrypted rlogin
krb524          4444/tcp                # Kerberos 5 to 4 ticket translator
```

By default, Kerberos V5 `telnet` and `ftp` use the same ports as the standard `telnet` and `ftp` programs, so if you already allow telnet and ftp connections through your firewall, the Kerberos V5 versions will get through as well. If you do not already allow telnet and ftp connections through your firewall, but need your users to be able to use Kerberos V5 telnet and ftp, you can either allow ftp and telnet connections on the standard ports, or switch these programs to non-default port numbers and allow ftp and telnet connections on those ports to get through.

Kerberos V5 `rlogin` uses the `klogin` service, which by default uses port 543. Encrypted Kerberos V5 rlogin uses uses the `eklogin` service, which by default uses port 2105.

Kerberos V5 `rsh` uses the `kshell` service, which by default uses port 544. However, the server must be able to make a TCP connection from the kshell port to an arbitrary port on the client, so

if your users are to be able to use `rsh` from outside your firewall, the server they connect to must be able to send outgoing packets to arbitrary port numbers. Similarly, if your users need to run `rsh` from inside your firewall to hosts outside your firewall, the outside server needs to be able to connect to an arbitrary port on the machine inside your firewall. Because Kerberos V5 `rcp` uses `rsh`, the same issues apply. If you need to use `rsh` (or `rcp`) through your firewall and are concerned with the security implications of allowing connections to arbitrary ports, MIT suggests that you have rules that specifically name these applications and, if possible, list the allowed hosts.

A reasonably good cookbook for configuring firewalls is available by FTP from `ftp.livingston.com`, in the location: `/pub/firewall/firewall-1.1.ps.Z`. The book *UNIX System Security*, by David Curry, is also a good starting point.

5 Backups of Secure Hosts

When you back up a secure host, you should exclude the host's keytab file from the backup. If someone obtained a copy of the keytab from a backup, that person could make any host masquerade as the host whose keytab was compromised. This could be particularly dangerous if the compromised keytab was from one of your KDCs. If the machine has a disk crash and the keytab file is lost, it is easy to generate another keytab file. (See Section 4.1.1 [Adding Principals to Keytabs], page 23.) If you are unable to exclude particular files from backups, you should ensure that the backups are kept as secure as the host's root password.

5.1 Backing Up the Kerberos Database

As with any file, it is possible that your Kerberos database could become corrupted. If this happens on one of the slave KDCs, you might never notice, since the next automatic propagation of the database would install a fresh copy. However, if it happens to the master KDC, the corrupted database would be propagated to all of the slaves during the next propagation. For this reason, MIT recommends that you back up your Kerberos database regularly. Because the master KDC is continuously dumping the database to a file in order to propagate it to the slave KDCs, it is a simple matter to have a cron job periodically copy the dump file to a secure machine elsewhere on your network. (Of course, it is important to make the host where these backups are stored as secure as your KDCs, and to encrypt its transmission across your network.) Then if your database becomes corrupted, you can load the most recent dump onto the master KDC. (See Section 3.6 [Restoring a Kerberos Database from a Dump File], page 19.)

6 Bug Reporting

In any complex software, there will be bugs. Please send bug reports or other problems you may uncover to the e-mail address **krb5-bugs@mit.edu**. Please mention which version of the Kerberos V5 distribution you are using, and whether you have made any private changes. Bug reports that include proposed fixes are especially welcome. If you do include fixes, please send them using either context diffs or unified diffs (using '`diff -c`' or '`diff -u`', respectively).

Appendix A Appendix

A.1 Files

A.2 krb5.conf

Normally, you should install your `krb5.conf` file in the directory `/etc`. However, note that you can override this default through the environment variable '`KRB5_CONFIG`'.

Here is an example of a generic `krb5.conf` file:

```
[libdefaults]
    ticket_lifetime = 600
    default_realm = ATHENA.MIT.EDU
    default_tkt_enctypes = des-cbc-crc
    default_tgs_enctypes = des-cbc-crc

[realms]
    ATHENA.MIT.EDU = {
        kdc = kerberos.mit.edu:88
        kdc = kerberos-1.mit.edu:88
        kdc = kerberos-2.mit.edu:88
        admin_server = kerberos.mit.edu:749
        default_domain = mit.edu
        }
    }

[domain_realm]
    .mit.edu = ATHENA.MIT.EDU
    mit.edu = ATHENA.MIT.EDU

[logging]
    kdc = FILE:/dev/ttyp9
    admin_server = FILE:/dev/ttyp9
    default = FILE:/dev/ttyp9
```

Here is an example of a more extensive `krb5.conf` file, which includes a second Kerberos realm and authentication to Kerberos V4 as well as V5 KDCs in the realm `ATHENA.MIT.EDU`:

```
[libdefaults]
    ticket_lifetime = 600
    default_realm = ATHENA.MIT.EDU
    default_tkt_enctypes = des-cbc-crc
    default_tgs_enctypes = des-cbc-crc
    krb4_srvtab = /etc/srvtab
    krb4_config = /usr/krb4/lib/krb.conf
    krb4_realms = /usr/krb4/lib/krb.realms

[realms]
    ATHENA.MIT.EDU = {
        kdc = kerberos.mit.edu:88
        kdc = kerberos-1.mit.edu:88
        kdc = kerberos-2.mit.edu:88
        admin_server = kerberos.mit.edu:749
        default_domain = mit.edu
        v4_instance_convert = {
            bleep = mit.edu
        }
    }
    FUBAR.ORG = {
        kdc = kerberos.fubar.org
        kdc = kerberos-1.fubar.org
        admin_server = kerberos.fubar.org
    }

[domain_realm]
    .mit.edu = ATHENA.MIT.EDU
    mit.edu = ATHENA.MIT.EDU
    .fubar.org = FUBAR.ORG
    fubar.org = FUBAR.ORG
```

For the KDCs, add a section onto the end of the `krb5.conf` file telling where the `kdc.conf` file is located, as in the following example:

```
[kdc]
    profile = /usr/krb5/lib/krb5kdc/kdc.conf

[logging]
    admin_server = FILE:/usr/krb5/lib/krb5kdc/kadmind.log
    kdc = FILE:/usr/krb5/lib/krb5kdc/kdc.log
    default = CONSOLE
```

A.3 kdc.conf

Normally, you should install your `kdc.conf` file in the directory `/usr/krb5/lib/krb5kdc`. However, note that you can override this default by a pointer in the KDC's `krb5.conf` file, or through the environment variable '`KRB5_KDC_PROFILE`'.

Here's an example of a `kdc.conf` file:

```
[kdcdefaults]
    kdc_ports = 88,750

[realms]
    ATHENA.MIT.EDU = {
        profile = /etc/krb5.conf
        database_name = /usr/krb5/lib/krb5kdc/principal
        admin_database_name = /usr/krb5/lib/krb5kdc/principal.kadm5
        admin_database_lockfile = /usr/krb5/lib/krb5kdc/principal.kadm5.lock
        admin_keytab = /usr/krb5/lib/krb5kdc/kadm5.keytab
        acl_file = /usr/krb5/lib/krb5kdc/kadm5.acl
        dict_file = /usr/krb5/lib/krb5kdc/kadm5.dict
        key_stash_file = /usr/krb5/lib/krb5kdc/.k5.ATHENA.MIT.EDU
        kadmind_port = 749
        max_life = 10h 0m 0s
        max_renewable_life = 7d 0h 0m 0s
        master_key_type = des-cbc-crc
        supported_enctypes = des-cbc-crc:normal
    }
```

To add Kerberos V4 support, change the `supported_enctypes` line to:

```
        supported_enctypes = des-cbc-crc:normal des-cbc-crc:v4
```

A.4 Kerberos Error Messages

A.4.1 Kerberos V5 Library Error Codes

This is the Kerberos v5 library error code table. Protocol error codes are ERROR_TABLE_BASE_krb5 + the protocol error code number; other error codes start at ERROR_TABLE_BASE_krb5 + 128.

0. KRB5KDC_ERR_NONE: No error
1. KRB5KDC_ERR_NAME_EXP: Client's entry in database has expired
2. KRB5KDC_ERR_SERVICE_EXP: Server's entry in database has expired
3. KRB5KDC_ERR_BAD_PVNO: Requested protocol version not supported
4. KRB5KDC_ERR_C_OLD_MAST_KVNO: Client's key is encrypted in an old master key
5. KRB5KDC_ERR_S_OLD_MAST_KVNO: Server's key is encrypted in an old master key

6. KRB5KDC_ERR_C_PRINCIPAL_UNKNOWN: Client not found in Kerberos database
7. KRB5KDC_ERR_S_PRINCIPAL_UNKNOWN: Server not found in Kerberos database
8. KRB5KDC_ERR_PRINCIPAL_NOT_UNIQUE: Principal has multiple entries in Kerberos database
9. KRB5KDC_ERR_NULL_KEY: Client or server has a null key
10. KRB5KDC_ERR_CANNOT_POSTDATE: Ticket is ineligible for postdating
11. KRB5KDC_ERR_NEVER_VALID: Requested effective lifetime is negative or too short
12. KRB5KDC_ERR_POLICY: KDC policy rejects request
13. KRB5KDC_ERR_BADOPTION: KDC can't fulfill requested option
14. KRB5KDC_ERR_ETYPE_NOSUPP: KDC has no support for encryption type
15. KRB5KDC_ERR_SUMTYPE_NOSUPP: KDC has no support for checksum type
16. KRB5KDC_ERR_PADATA_TYPE_NOSUPP: KDC has no support for padata type
17. KRB5KDC_ERR_TRTYPE_NOSUPP: KDC has no support for transited type
18. KRB5KDC_ERR_CLIENT_REVOKED: Clients credentials have been revoked
19. KRB5KDC_ERR_SERVICE_REVOKED: Credentials for server have been revoked
20. KRB5KDC_ERR_TGT_REVOKED: TGT has been revoked
21. KRB5KDC_ERR_CLIENT_NOTYET: Client not yet valid - try again later
22. KRB5KDC_ERR_SERVICE_NOTYET: Server not yet valid - try again later
23. KRB5KDC_ERR_KEY_EXP: Password has expired
24. KRB5KDC_ERR_PREAUTH_FAILED: Preauthentication failed
25. KRB5KDC_ERR_PREAUTH_REQUIRED: Additional pre-authentication required
26. KRB5KDC_ERR_SERVER_NOMATCH: Requested server and ticket don't match
27. KRB5PLACEHOLD_27: KRB5 error code 27
28. KRB5PLACEHOLD_28: KRB5 error code 28
29. KRB5PLACEHOLD_29: KRB5 error code 29
30. KRB5PLACEHOLD_30: KRB5 error code 30
31. KRB5KRB_AP_ERR_BAD_INTEGRITY: Decrypt integrity check failed
32. KRB5KRB_AP_ERR_TKT_EXPIRED: Ticket expired
33. KRB5KRB_AP_ERR_TKT_NYV: Ticket not yet valid
34. KRB5KRB_AP_ERR_REPEAT: Request is a replay
35. KRB5KRB_AP_ERR_NOT_US: The ticket isn't for us
36. KRB5KRB_AP_ERR_BADMATCH: Ticket/authenticator don't match
37. KRB5KRB_AP_ERR_SKEW: Clock skew too great
38. KRB5KRB_AP_ERR_BADADDR: Incorrect net address

39. KRB5KRB_AP_ERR_BADVERSION: Protocol version mismatch
40. KRB5KRB_AP_ERR_MSG_TYPE: Invalid message type
41. KRB5KRB_AP_ERR_MODIFIED: Message stream modified
42. KRB5KRB_AP_ERR_BADORDER: Message out of order
43. KRB5KRB_AP_ERR_ILL_CR_TKT: Illegal cross-realm ticket
44. KRB5KRB_AP_ERR_BADKEYVER: Key version is not available
45. KRB5KRB_AP_ERR_NOKEY: Service key not available
46. KRB5KRB_AP_ERR_MUT_FAIL: Mutual authentication failed
47. KRB5KRB_AP_ERR_BADDIRECTION: Incorrect message direction
48. KRB5KRB_AP_ERR_METHOD: Alternative authentication method required
49. KRB5KRB_AP_ERR_BADSEQ: Incorrect sequence number in message
50. KRB5KRB_AP_ERR_INAPP_CKSUM: Inappropriate type of checksum in message
51. KRB5PLACEHOLD_51: KRB5 error code 51
52. KRB5PLACEHOLD_52: KRB5 error code 52
53. KRB5PLACEHOLD_53: KRB5 error code 53
54. KRB5PLACEHOLD_54: KRB5 error code 54
55. KRB5PLACEHOLD_55: KRB5 error code 55
56. KRB5PLACEHOLD_56: KRB5 error code 56
57. KRB5PLACEHOLD_57: KRB5 error code 57
58. KRB5PLACEHOLD_58: KRB5 error code 58
59. KRB5PLACEHOLD_59: KRB5 error code 59
60. KRB5KRB_ERR_GENERIC: Generic error (see e-text)
61. KRB5KRB_ERR_FIELD_TOOLONG: Field is too long for this implementation
62. KRB5PLACEHOLD_62: KRB5 error code 62
63. KRB5PLACEHOLD_63: KRB5 error code 63
64. KRB5PLACEHOLD_64: KRB5 error code 64
65. KRB5PLACEHOLD_65: KRB5 error code 65
66. KRB5PLACEHOLD_66: KRB5 error code 66
67. KRB5PLACEHOLD_67: KRB5 error code 67
68. KRB5PLACEHOLD_68: KRB5 error code 68
69. KRB5PLACEHOLD_69: KRB5 error code 69
70. KRB5PLACEHOLD_70: KRB5 error code 70
71. KRB5PLACEHOLD_71: KRB5 error code 71
72. KRB5PLACEHOLD_72: KRB5 error code 72

73. KRB5PLACEHOLD_73: KRB5 error code 73
74. KRB5PLACEHOLD_74: KRB5 error code 74
75. KRB5PLACEHOLD_75: KRB5 error code 75
76. KRB5PLACEHOLD_76: KRB5 error code 76
77. KRB5PLACEHOLD_77: KRB5 error code 77
78. KRB5PLACEHOLD_78: KRB5 error code 78
79. KRB5PLACEHOLD_79: KRB5 error code 79
80. KRB5PLACEHOLD_80: KRB5 error code 80
81. KRB5PLACEHOLD_81: KRB5 error code 81
82. KRB5PLACEHOLD_82: KRB5 error code 82
83. KRB5PLACEHOLD_83: KRB5 error code 83
84. KRB5PLACEHOLD_84: KRB5 error code 84
85. KRB5PLACEHOLD_85: KRB5 error code 85
86. KRB5PLACEHOLD_86: KRB5 error code 86
87. KRB5PLACEHOLD_87: KRB5 error code 87
88. KRB5PLACEHOLD_88: KRB5 error code 88
89. KRB5PLACEHOLD_89: KRB5 error code 89
90. KRB5PLACEHOLD_90: KRB5 error code 90
91. KRB5PLACEHOLD_91: KRB5 error code 91
92. KRB5PLACEHOLD_92: KRB5 error code 92
93. KRB5PLACEHOLD_93: KRB5 error code 93
94. KRB5PLACEHOLD_94: KRB5 error code 94
95. KRB5PLACEHOLD_95: KRB5 error code 95
96. KRB5PLACEHOLD_96: KRB5 error code 96
97. KRB5PLACEHOLD_97: KRB5 error code 97
98. KRB5PLACEHOLD_98: KRB5 error code 98
99. KRB5PLACEHOLD_99: KRB5 error code 99
100. KRB5PLACEHOLD_100: KRB5 error code 100
101. KRB5PLACEHOLD_101: KRB5 error code 101
102. KRB5PLACEHOLD_102: KRB5 error code 102
103. KRB5PLACEHOLD_103: KRB5 error code 103
104. KRB5PLACEHOLD_104: KRB5 error code 104
105. KRB5PLACEHOLD_105: KRB5 error code 105
106. KRB5PLACEHOLD_106: KRB5 error code 106

107. KRB5PLACEHOLD_107: KRB5 error code 107
108. KRB5PLACEHOLD_108: KRB5 error code 108
109. KRB5PLACEHOLD_109: KRB5 error code 109
110. KRB5PLACEHOLD_110: KRB5 error code 110
111. KRB5PLACEHOLD_111: KRB5 error code 111
112. + KRB5PLACEHOLD_112: KRB5 error code 112
113. KRB5PLACEHOLD_113: KRB5 error code 113
114. KRB5PLACEHOLD_114: KRB5 error code 114
115. KRB5PLACEHOLD_115: KRB5 error code 115
116. KRB5PLACEHOLD_116: KRB5 error code 116
117. KRB5PLACEHOLD_117: KRB5 error code 117
118. KRB5PLACEHOLD_118: KRB5 error code 118
119. KRB5PLACEHOLD_119: KRB5 error code 119
120. KRB5PLACEHOLD_120: KRB5 error code 120
121. KRB5PLACEHOLD_121: KRB5 error code 121
122. KRB5PLACEHOLD_122: KRB5 error code 122
123. KRB5PLACEHOLD_123: KRB5 error code 123
124. KRB5PLACEHOLD_124: KRB5 error code 124
125. KRB5PLACEHOLD_125: KRB5 error code 125
126. KRB5PLACEHOLD_126: KRB5 error code 126
127. KRB5PLACEHOLD_127: KRB5 error code 127
128. KRB5_ERR_RCSID: $Id: admin.texinfo,v 1.7 1996/09/09 18:29:25 jcb Exp $
129. KRB5_LIBOS_BADLOCKFLAG: Invalid flag for file lock mode
130. KRB5_LIBOS_CANTREADPWD: Cannot read password
131. KRB5_LIBOS_BADPWDMATCH: Password mismatch
132. KRB5_LIBOS_PWDINTR: Password read interrupted
133. KRB5_PARSE_ILLCHAR: Illegal character in component name
134. KRB5_PARSE_MALFORMED: Malformed representation of principal
135. KRB5_CONFIG_CANTOPEN: Can't open/find configuration file
136. KRB5_CONFIG_BADFORMAT: Improper format of configuration file
137. KRB5_CONFIG_NOTENUFSPACE: Insufficient space to return complete information
138. KRB5_BADMSGTYPE: Invalid message type specified for encoding
139. KRB5_CC_BADNAME: Credential cache name malformed
140. KRB5_CC_UNKNOWN_TYPE: Unknown credential cache type

141. KRB5_CC_NOTFOUND: Matching credential not found
142. KRB5_CC_END: End of credential cache reached
143. KRB5_NO_TKT_SUPPLIED: Request did not supply a ticket
144. KRB5KRB_AP_WRONG_PRINC: Wrong principal in request
145. KRB5KRB_AP_ERR_TKT_INVALID: Ticket has invalid flag set
146. KRB5_PRINC_NOMATCH: Requested principal and ticket don't match
147. KRB5_KDCREP_MODIFIED: KDC reply did not match expectations
148. KRB5_KDCREP_SKEW: Clock skew too great in KDC reply
149. KRB5_IN_TKT_REALM_MISMATCH: Client/server realm mismatch in initial ticket request
150. KRB5_PROG_ETYPE_NOSUPP: Program lacks support for encryption type
151. KRB5_PROG_KEYTYPE_NOSUPP: Program lacks support for key type
152. KRB5_WRONG_ETYPE: Requested encryption type not used in message
153. KRB5_PROG_SUMTYPE_NOSUPP: Program lacks support for checksum type
154. KRB5_REALM_UNKNOWN: Cannot find KDC for requested realm
155. KRB5_SERVICE_UNKNOWN: Kerberos service unknown
156. KRB5_KDC_UNREACH: Cannot contact any KDC for requested realm
157. KRB5_NO_LOCALNAME: No local name found for principal name
158. KRB5_MUTUAL_FAILED: Mutual authentication failed
159. KRB5_RC_TYPE_EXISTS: Replay cache type is already registered
160. KRB5_RC_MALLOC: No more memory to allocate (in replay cache code)
161. KRB5_RC_TYPE_NOTFOUND: Replay cache type is unknown
162. KRB5_RC_UNKNOWN: Generic unknown RC error
163. KRB5_RC_REPLAY: Message is a replay
164. KRB5_RC_IO: Replay I/O operation failed XXX
165. KRB5_RC_NOIO: Replay cache type does not support non-volatile storage
166. KRB5_RC_PARSE: Replay cache name parse/format error
167. KRB5_RC_IO_EOF: End-of-file on replay cache I/O
168. KRB5_RC_IO_MALLOC: No more memory to allocate (in replay cache I/O code)
169. KRB5_RC_IO_PERM: Permission denied in replay cache code
170. KRB5_RC_IO_IO: I/O error in replay cache i/o code
171. KRB5_RC_IO_UNKNOWN: Generic unknown RC/IO error
172. KRB5_RC_IO_SPACE: Insufficient system space to store replay information
173. KRB5_TRANS_CANTOPEN: Can't open/find realm translation file
174. KRB5_TRANS_BADFORMAT: Improper format of realm translation file

175. KRB5_LNAME_CANTOPEN: Can't open/find lname translation database
176. KRB5_LNAME_NOTRANS: No translation available for requested principal
177. KRB5_LNAME_BADFORMAT: Improper format of translation database entry
178. KRB5_CRYPTO_INTERNAL: Cryptosystem internal error
179. KRB5_KT_BADNAME: Key table name malformed
180. KRB5_KT_UNKNOWN_TYPE: Unknown Key table type
181. KRB5_KT_NOTFOUND: Key table entry not found
182. KRB5_KT_END: End of key table reached
183. KRB5_KT_NOWRITE: Cannot write to specified key table
184. KRB5_KT_IOERR: Error writing to key table
185. KRB5_NO_TKT_IN_RLM: Cannot find ticket for requested realm
186. KRB5DES_BAD_KEYPAR: DES key has bad parity
187. KRB5DES_WEAK_KEY: DES key is a weak key
188. KRB5_BAD_ENCTYPE: Bad encryption type
189. KRB5_BAD_KEYSIZE: Key size is incompatible with encryption type
190. KRB5_BAD_MSIZE: Message size is incompatible with encryption type
191. KRB5_CC_TYPE_EXISTS: Credentials cache type is already registered.
192. KRB5_KT_TYPE_EXISTS: Key table type is already registered.
193. KRB5_CC_IO: Credentials cache I/O operation failed XXX
194. KRB5_FCC_PERM: Credentials cache file permissions incorrect
195. KRB5_FCC_NOFILE: No credentials cache file found
196. KRB5_FCC_INTERNAL: Internal file credentials cache error
197. KRB5_CC_WRITE: Error writing to credentials cache file
198. KRB5_CC_NOMEM: No more memory to allocate (in credentials cache code)
199. KRB5_CC_FORMAT: Bad format in credentials cache
200. KRB5_INVALID_FLAGS: Invalid KDC option combination (library internal error) [for dual tgt library calls]
201. KRB5_NO_2ND_TKT: Request missing second ticket [for dual tgt library calls]
202. KRB5_NOCREDS_SUPPLIED: No credentials supplied to library routine
203. KRB5_SENDAUTH_BADAUTHVERS: Bad sendauth version was sent
204. KRB5_SENDAUTH_BADAPPLVERS: Bad application version was sent (via sendauth)
205. KRB5_SENDAUTH_BADRESPONSE: Bad response (during sendauth exchange)
206. KRB5_SENDAUTH_REJECTED: Server rejected authentication (during sendauth exchange)
207. KRB5_PREAUTH_BAD_TYPE: Unsupported preauthentication type

208. KRB5_PREAUTH_NO_KEY: Required preauthentication key not supplied
209. KRB5_PREAUTH_FAILED: Generic preauthentication failure
210. KRB5_RCACHE_BADVNO: Unsupported replay cache format version number
211. KRB5_CCACHE_BADVNO: Unsupported credentials cache format version number
212. KRB5_KEYTAB_BADVNO: Unsupported key table format version number
213. KRB5_PROG_ATYPE_NOSUPP: Program lacks support for address type
214. KRB5_RC_REQUIRED: Message replay detection requires rcache parameter
215. KRB5_ERR_BAD_HOSTNAME: Hostname cannot be canonicalized
216. KRB5_ERR_HOST_REALM_UNKNOWN: Cannot determine realm for host
217. KRB5_SNAME_UNSUPP_NAMETYPE: Conversion to service principal undefined for name type
218. KRB5KRB_AP_ERR_V4_REPLY: Initial Ticket response appears to be Version 4 error
219. KRB5_REALM_CANT_RESOLVE: Cannot resolve KDC for requested realm
220. KRB5_TKT_NOT_FORWARDABLE: Requesting ticket can't get forwardable tickets
221. KRB5_FWD_BAD_PRINCIPAL: Bad principal name while trying to forward credentials
222. KRB5_GET_IN_TKT_LOOP: Looping detected inside krb5_get_in_tkt
223. KRB5_CONFIG_NODEFREALM: Configuration file does not specify default realm
224. KRB5_SAM_UNSUPPORTED: Bad SAM flags in obtain_sam_padata

A.4.2 Kerberos V5 Database Library Error Codes

This is the Kerberos v5 database library error code table.

0. KRB5_KDB_RCSID: $Id: admin.texinfo,v 1.7 1996/09/09 18:29:25 jcb Exp $
1. KRB5_KDB_INUSE: Entry already exists in database
2. KRB5_KDB_UK_SERROR: Database store error
3. KRB5_KDB_UK_RERROR: Database read error
4. KRB5_KDB_UNAUTH: Insufficient access to perform requested operation
5. KRB5_KDB_NOENTRY: No such entry in the database
6. KRB5_KDB_ILL_WILDCARD: Illegal use of wildcard
7. KRB5_KDB_DB_INUSE: Database is locked or in use–try again later
8. KRB5_KDB_DB_CHANGED: Database was modified during read
9. KRB5_KDB_TRUNCATED_RECORD: Database record is incomplete or corrupted
10. KRB5_KDB_RECURSIVELOCK: Attempt to lock database twice
11. KRB5_KDB_NOTLOCKED: Attempt to unlock database when not locked
12. KRB5_KDB_BADLOCKMODE: Invalid kdb lock mode

13. KRB5_KDB_DBNOTINITED: Database has not been initialized
14. KRB5_KDB_DBINITED: Database has already been initialized
15. KRB5_KDB_ILLDIRECTION: Bad direction for converting keys
16. KRB5_KDB_NOMASTERKEY: Cannot find master key record in database
17. KRB5_KDB_BADMASTERKEY: Master key does not match database
18. KRB5_KDB_INVALIDKEYSIZE: Key size in database is invalid
19. KRB5_KDB_CANTREAD_STORED: Cannot find/read stored master key
20. KRB5_KDB_BADSTORED_MKEY: Stored master key is corrupted
21. KRB5_KDB_CANTLOCK_DB: Insufficient access to lock database
22. KRB5_KDB_DB_CORRUPT: Database format error
23. KRB5_KDB_BAD_VERSION: Unsupported version in database entry
24. KRB5_KDB_BAD_SALTTYPE: Unsupported salt type
25. KRB5_KDB_BAD_ENCTYPE: Unsupported encryption type

A.4.3 Kerberos V5 Magic Numbers Error Codes

This is the Kerberos v5 magic numbers error code table.

0. KV5M_NONE: Kerberos V5 magic number table
1. KV5M_PRINCIPAL: Bad magic number for krb5_principal structure
2. KV5M_DATA: Bad magic number for krb5_data structure
3. KV5M_KEYBLOCK: Bad magic number for krb5_keyblock structure
4. KV5M_CHECKSUM: Bad magic number for krb5_checksum structure
5. KV5M_ENCRYPT_BLOCK: Bad magic number for krb5_encrypt_block structure
6. KV5M_ENC_DATA: Bad magic number for krb5_enc_data structure
7. KV5M_CRYPTOSYSTEM_ENTRY: Bad magic number for krb5_cryptosystem_entry structure
8. KV5M_CS_TABLE_ENTRY: Bad magic number for krb5_cs_table_entry structure
9. KV5M_CHECKSUM_ENTRY: Bad magic number for krb5_checksum_entry structure
10. KV5M_AUTHDATA: Bad magic number for krb5_authdata structure
11. KV5M_TRANSITED: Bad magic number for krb5_transited structure
12. KV5M_ENC_TKT_PART: Bad magic number for krb5_enc_tkt_part structure
13. KV5M_TICKET: Bad magic number for krb5_ticket structure
14. KV5M_AUTHENTICATOR: Bad magic number for krb5_authenticator structure
15. KV5M_TKT_AUTHENT: Bad magic number for krb5_tkt_authent structure
16. KV5M_CREDS: Bad magic number for krb5_creds structure
17. KV5M_LAST_REQ_ENTRY: Bad magic number for krb5_last_req_entry structure

18. KV5M_PA_DATA: Bad magic number for krb5_pa_data structure
19. KV5M_KDC_REQ: Bad magic number for krb5_kdc_req structure
20. KV5M_ENC_KDC_REP_PART: Bad magic number for krb5_enc_kdc_rep_part structure
21. KV5M_KDC_REP: Bad magic number for krb5_kdc_rep structure
22. KV5M_ERROR: Bad magic number for krb5_error structure
23. KV5M_AP_REQ: Bad magic number for krb5_ap_req structure
24. KV5M_AP_REP: Bad magic number for krb5_ap_rep structure
25. KV5M_AP_REP_ENC_PART: Bad magic number for krb5_ap_rep_enc_part structure
26. KV5M_RESPONSE: Bad magic number for krb5_response structure
27. KV5M_SAFE: Bad magic number for krb5_safe structure
28. KV5M_PRIV: Bad magic number for krb5_priv structure
29. KV5M_PRIV_ENC_PART: Bad magic number for krb5_priv_enc_part structure
30. KV5M_CRED: Bad magic number for krb5_cred structure
31. KV5M_CRED_INFO: Bad magic number for krb5_cred_info structure
32. KV5M_CRED_ENC_PART: Bad magic number for krb5_cred_enc_part structure
33. KV5M_PWD_DATA: Bad magic number for krb5_pwd_data structure
34. KV5M_ADDRESS: Bad magic number for krb5_address structure
35. KV5M_KEYTAB_ENTRY: Bad magic number for krb5_keytab_entry structure
36. KV5M_CONTEXT: Bad magic number for krb5_context structure
37. KV5M_OS_CONTEXT: Bad magic number for krb5_os_context structure
38. KV5M_ALT_METHOD: Bad magic number for krb5_alt_method structure
39. KV5M_ETYPE_INFO_ENTRY: Bad magic number for krb5_etype_info_entry structure
40. KV5M_DB_CONTEXT: Bad magic number for krb5_db_context structure
41. KV5M_AUTH_CONTEXT: Bad magic number for krb5_auth_context structure
42. KV5M_KEYTAB: Bad magic number for krb5_keytab structure
43. KV5M_RCACHE: Bad magic number for krb5_rcache structure
44. KV5M_CCACHE: Bad magic number for krb5_ccache structure
45. KV5M_PREAUTH_OPS: Bad magic number for krb5_preauth_ops
46. KV5M_SAM_CHALLENGE: Bad magic number for krb5_sam_challenge
47. KV5M_SAM_KEY: Bad magic number for krb5_sam_key
48. KV5M_ENC_SAM_RESPONSE_ENC: Bad magic number for krb5_enc_sam_response_enc

49. KV5M_SAM_RESPONSE: Bad magic number for krb5_sam_response
50. KV5M_PREDICTED_SAM_RESPONSE: Bad magic number for krb5_predicted_sam_response
51. KV5M_PASSWD_PHRASE_ELEMENT: Bad magic number for passwd_phrase_element

A.4.4 ASN.1 Error Codes

0. ASN1_BAD_TIMEFORMAT: ASN.1 failed call to system time library
1. ASN1_MISSING_FIELD: ASN.1 structure is missing a required field
2. ASN1_MISPLACED_FIELD: ASN.1 unexpected field number
3. ASN1_TYPE_MISMATCH: ASN.1 type numbers are inconsistent
4. ASN1_OVERFLOW: ASN.1 value too large
5. ASN1_OVERRUN: ASN.1 encoding ended unexpectedly
6. ASN1_BAD_ID: ASN.1 identifier doesn't match expected value
7. ASN1_BAD_LENGTH: ASN.1 length doesn't match expected value
8. ASN1_BAD_FORMAT: ASN.1 badly-formatted encoding
9. ASN1_PARSE_ERROR: ASN.1 parse error

A.4.5 GSSAPI Error Codes

Generic GSSAPI Errors:

0. G_BAD_SERVICE_NAME: No in SERVICE-NAME name string
1. G_BAD_STRING_UID: STRING-UID-NAME contains nondigits
2. G_NOUSER: UID does not resolve to username
3. G_VALIDATE_FAILED: Validation error
4. G_BUFFER_ALLOC: Couldn't allocate gss_buffer_t data
5. G_BAD_MSG_CTX: Message context invalid
6. G_WRONG_SIZE: Buffer is the wrong size
7. G_BAD_USAGE: Credential usage type is unknown
8. G_UNKNOWN_QOP: Unknown quality of protection specified
9. G_BAD_HOSTNAME: Hostname in SERVICE-NAME string could not be canonicalized

Kerberos 5 GSSAPI Errors:

0. KG_CCACHE_NOMATCH: Principal in credential cache does not match desired name
1. KG_KEYTAB_NOMATCH: No principal in keytab matches desired name
2. KG_TGT_MISSING: Credential cache has no TGT

3. KG_NO_SUBKEY: Authenticator has no subkey
4. KG_CONTEXT_ESTABLISHED: Context is already fully established
5. KG_BAD_SIGN_TYPE: Unknown signature type in token
6. KG_BAD_LENGTH: Invalid field length in token
7. KG_CTX_INCOMPLETE: Attempt to use incomplete security context
8. KG_CONTEXT: Bad magic number for krb5_gss_ctx_id_t
9. KG_CRED: Bad magic number for krb5_gss_cred_id_t
10. KG_ENC_DESC: Bad magic number for krb5_gss_enc_desc

A.5 kadmin Time Zones

This is a complete listing of the time zones recognized by the `kadmin` command.

gmt	Greenwich Mean Time
ut, utc	Universal Time (Coordinated).
wet	Western European Time. (Same as GMT.)
bst	British Summer Time. (1 hour ahead of GMT.)
wat	West Africa Time. (1 hour behind GMT.)
at	Azores Time. (2 hours behind GMT.)
bst	Brazil Standard Time. (3 hours behind GMT.) Note that the abbreviation BST also stands for British Summer Time.
gst	Greenland Standard Time. (3 hours behind GMT.) Note that the abbreviation GST also stands for Guam Standard Time.
nft	Newfoundland Time. (3.5 hours behind GMT.)
nst	Newfoundland Standard Time. (3.5 hours behind GMT.)
ndt	Newfoundland Daylight Time. (2.5 hours behind GMT.)
ast	Atlantic Standard Time. (4 hours behind GMT.)
adt	Atlantic Daylight Time. (3 hours behind GMT.)
est	Eastern Standard Time. (5 hours behind GMT.)
edt	Eastern Daylight Time. (4 hours behind GMT.)
cst	Central Standard Time. (6 hours behind GMT.)
cdt	Central Daylight Time. (5 hours behind GMT.)
mst	Mountain Standard Time. (7 hours behind GMT.)
mdt	Mountain Daylight Time. (6 hours behind GMT.)
pst	Pacific Standard Time. (8 hours behind GMT.)
pdt	Pacific Daylight Time. (7 hours behind GMT.)
yst	Yukon Standard Time. (9 hours behind GMT.)
ydt	Yukon Daylight Time. (8 hours behind GMT.)
hst	Hawaii Standard Time. (10 hours behind GMT.)

hdt Hawaii Daylight Time. (9 hours behind GMT.)
cat Central Alaska Time. (10 hours behind GMT.)
ahst Alaska-Hawaii Standard Time. (10 hours behind GMT.)
nt Nome Time. (11 hours behind GMT.)
idlw International Date Line West Time. (12 hours behind GMT.)
cet Central European Time. (1 hour ahead of GMT.)
met Middle European Time. (1 hour ahead of GMT.)
mewt Middle European Winter Time. (1 hour ahead of GMT.)
mest Middle European Summer Time. (2 hours ahead of GMT.)
swt Swedish Winter Time. (1 hour ahead of GMT.)
sst Swedish Summer Time. (1 hours ahead of GMT.)
fwt French Winter Time. (1 hour ahead of GMT.)
fst French Summer Time. (2 hours ahead of GMT.)
eet Eastern Europe Time; Russia Zone 1. (2 hours ahead of GMT.)
bt Baghdad Time; Russia Zone 2. (3 hours ahead of GMT.)
it Iran Time. (3.5 hours ahead of GMT.)
zp4 Russia Zone 3. (4 hours ahead of GMT.)
zp5 Russia Zone 4. (5 hours ahead of GMT.)
ist Indian Standard Time. (5.5 hours ahead of GMT.)
zp6 Russia Zone 5. (6 hours ahead of GMT.)
nst North Sumatra Time. (6.5 hours ahead of GMT.) Note that the abbreviation NST is also used for Newfoundland Stanard Time.
sst South Sumatra Time; Russia Zone 6. (7 hours ahead of GMT.) Note that SST is also Swedish Summer Time.
wast West Australian Standard Time. (7 hours ahead of GMT.)
wadt West Australian Daylight Time. (8 hours ahead of GMT.)
jt Java Time. (7.5 hours ahead of GMT.)
cct China Coast Time; Russia Zone 7. (8 hours ahead of GMT.)
jst Japan Standard time; Russia Zone 8. (9 hours ahead of GMT.)
kst Korean Standard Time. (9 hours ahead of GMT.)
cast Central Australian Standard Time. (9.5 hours ahead of GMT.)
cadt Central Australian Daylight Time. (10.5 hours ahead of GMT.)
east Eastern Australian Standard Time. (10 hours ahead of GMT.)
eadt Eastern Australian Daylight Time. (11 hours ahead of GMT.)
gst Guam Standard Time; Russia Zone 9. (10 hours ahead of GMT.)
kdt Korean Daylight Time. (10 hours ahead of GMT.)
nzt New Zealand Time. (12 hours ahead of GMT.)
nzst New Zealand Standard Time. (12 hours ahead of GMT.)
nzdt New Zealand Daylight Time. (13 hours ahead of GMT.)
idle International Date Line East. (12 hours ahead of GMT.)

Table of Contents

1 Introduction 1

1.1 Why Should I use Kerberos? 1
1.2 Kerberos V5 Documentation 1
1.3 Overview of This Guide 1

2 How Kerberos Works 3

2.1 Network Services and Their Client Programs 3
2.2 Kerberos Tickets 3
2.3 The Kerberos Database 3
2.4 Kerberos Realms 4
2.5 The Ticket-Granting Ticket 4
2.6 Network Services and the Master Database 4
2.6.1 The Keytab File 5
2.7 The User–Kerberos Interaction 5
2.8 Definitions 6

3 Administrating the Kerberos Database 7

3.1 Kadmin Options 7
3.2 Date Format 8
3.3 Principals 9
3.3.1 Retrieving Information About a Principal 9
3.3.1.1 Attributes 9
3.3.1.2 Retrieving a List of Principals 10
3.3.2 Privileges 10
3.3.3 Adding or Modifying Principals 11
3.3.4 Deleting Principals 14
3.3.5 Changing Passwords 15
3.3.6 Renaming Principals 16
3.4 Policies 16
3.4.1 Retrieving Policies 16
3.4.2 Retrieving the List of Policies 17
3.4.3 Adding or Modifying Policies 17
3.4.4 Deleting Policies 18
3.5 Dumping a Kerberos Database to a File 18
3.6 Restoring a Kerberos Database from a Dump File 19
3.7 Creating a Stash File 20
3.8 Creating and Destroying a Kerberos Database 20

4 Application Servers 23
4.1 Keytabs 23
4.1.1 Adding Principals to Keytabs 23
4.1.2 Removing Principals from Keytabs 24
4.2 Clock Skew 24
4.3 Getting DNS Information Correct 25
4.4 Configuring Your Firewall to Work With Kerberos V5 26

5 Backups of Secure Hosts 29
5.1 Backing Up the Kerberos Database 29

6 Bug Reporting 31

Appendix A Appendix 33
A.1 Files 33
A.2 krb5.conf 33
A.3 kdc.conf 35
A.4 Kerberos Error Messages 35
A.4.1 Kerberos V5 Library Error Codes 35
A.4.2 Kerberos V5 Database Library Error Codes 42
A.4.3 Kerberos V5 Magic Numbers Error Codes 43
A.4.4 ASN.1 Error Codes 45
A.4.5 GSSAPI Error Codes 45
A.5 kadmin Time Zones 46